



MAJIK 140

OVERVIEW

High performance 4-way floorstanding loudspeaker

KEY FEATURES INCLUDE

- 2K driver array for clean and pure high-frequency reproduction and flexible in-room positioning
- High quality composite-cone drive units deliver pitch-accurate musical bass
- Single port with unique "rifled" design for deep and extended bass
- High quality crossovers ensure accurate music reproduction across the full frequency range
- Simple upgrade path from single to multi-wiring /amping to fully Aktiv configuration

Majik 140 is a 4-way floorstanding loudspeaker which delivers exceptional musical performance.

Majik 140 features Linn's 2K driver array - an evolution of the array technology found in Linn's highest performing loudspeakers. This technology houses the high-frequency drive-units in a dedicated cast alloy chassis, to create a wonderfully clean and pure high frequency reproduction. The unique design of the 2K driver array provides even dispersion for exceptional performance, regardless of where the loudspeakers are placed in a room.

Even higher levels of performance can be easily achieved by simply bi-wiring through to fully Aktiv configuration.

Solid metal upgrade stands are available to purchase separately to provide improved stability for even higher audio performance. An optional $\frac{3}{4}$ length grille is also available. The grille uses Linn's invisible, flush fitting "SEKRIT-Fastener" fixing method, as used for the Akurate loudspeaker.

Available in a choice of high-grade, real-wood veneer finishes, the timeless design of Majik 140 will enhance your living space.

Majik 140 perfectly complements other components in the Linn Majik range, combining premium audio performance with unbeatable value.



1

MAJIK 140

TECHNICAL SPECIFICATION

High performance 4-way floorstanding loudspeaker

■ Date of Introduction	October 2007
■ Type	4-way floorstanding loudspeaker
■ Overall sizes incl. supplied stand	(H) 975 mm x (W) 250 mm x (D) 335 mm (H) 38 $\frac{3}{8}$ inches x (W) 9 $\frac{7}{8}$ inches x (D) 13 $\frac{1}{4}$ inches
■ Weight (with supplied stand)	21.3 kg 47 lbs
■ Cabinet volume	40 litres
■ Impedance (passive)	4 Ω
■ Impedance (Aktiv bass)	8 Ω
■ Impedance (Aktiv midrange)	8 Ω
■ Impedance (Aktiv tweeter)	7 Ω
■ Impedance (Aktiv super-tweeter)	7 Ω
■ Efficiency	88 dB for 1 watt at 1 metre (1 kHz)
■ Frequency response (Passive)	55 Hz - 20 kHz
■ Frequency response (Aktiv)	55 Hz - 20 kHz
■ Crossover options	Passive or fully Aktiv
■ Connection options	Single, bi-, tri- or quad- wire / amp; four-way Aktiv Binding posts can accept 4mm banana plugs, bare wire and spades
■ Optional bass reduction	2 dB
■ Finishes	Cherry, Oak, Walnut, Black Ash, White

The above information is subject to change without prior notice.

Linn Products Limited
Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK.
Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: helpline@linn.co.uk, Website: www.linn.co.uk

Linn Products Inc
8787 Perimeter Park Boulevard, Jacksonville FL 32216, USA.
Telephone: +1 (904) 645 5242, Facsimile: +1 (904) 645 7275, Helpline: 888-671-LINN, E-mail: helpline@linninc.com, Website: www.linninc.com

Linn Deutschland GmbH
Hühnerposten 1d, 20097 Hamburg, Deutschland.
Telephone: +49 (0) 40 890 660 0, Facsimile: +49 (0) 40 890 660 29, E-mail: info@linngmbh.de, Website: www.linn.co.uk

Linn Records Limited
Glasgow Road, Waterfoot, Eaglesham, Glasgow G76 0EQ, Scotland, UK.
Telephone: +44 (0) 141 303 5027/5029, Facsimile: +44 (0) 141 303 5007, E-mail: info@linnrecords.co.uk, Website: www.linnrecords.com

Copyright © 2007, Linn Products Limited. All rights reserved.
Linn, the Linn logo and all other Linn product names and slogans are trade marks or registered trade marks of Linn Products Limited, registered in at least the UK and/or the EU.
Linn Products Limited disclaims any proprietary interest in trade marks and trade names other than its own.